



Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Danbury, CT 06810
Suite 300
Tel. 1-203-205-2900

1. Product And Company Identification

Product Name: ARMOR ALL® Custom Shield – White

Responsible Party: The Armor All/STP Products Company
44 Old Ridgebury Road
Suite 300
Danbury, CT 06810

Information Phone Number: +1 203-205-2900

Emergency Phone Number:

For Medical Emergencies, call 1-866-949-6465 / +1 303-389-1332 (Outside US and Canada)
For Transportation Emergencies, call 1-800-424-9300 (Chemtrec) +1-703-527-3887 for
Outside US and Canada (call collect)

MSDS Date Of Preparation: 01/31/13

Product Use: Automotive maintenance product: Rubber coating – For consumer and professional use

2. Hazards Identification

EMERGENCY OVERVIEW DANGER!

Extremely flammable aerosol. Contents under pressure. Extremely Flammable Liquid and Vapor. May cause eye, skin and respiratory tract irritation. Inhalation of mists or vapors may cause respiratory irritation and central nervous system effects such as dizziness, drowsiness, headache and nausea. Harmful or fatal if swallowed. Aspiration into the lungs during swallowing or vomiting may cause lung damage. Ingestion may also cause gastrointestinal effects such as nausea, vomiting and diarrhea and central nervous system effects. Avoid eye contact. Use only with adequate ventilation. Keep away from heat, sparks and all other sources of ignition.

3. Composition/Information On Ingredients

Component	CAS No.	Amount
Propane	74-98-6	25-27
VM&P Naphtha	64742-89-8	23-25
Heptane	426260-76-6	13-15
N-Butane	106-97-8	8-10
Xylene	1330-20-7	5-7
Methyl Ethyl Ketone	78-93-3	2-4
Methyl n-Amyl Ketone	110-43-0	2-4
Ethyl benzene	100-41-4	1-2

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. If breathing has stopped, administer artificial respiration. Get medical attention if symptoms appear and persist.

Skin Contact: Remove contaminated clothing and launder before reuse. Wash exposed skin with soap and water. If skin irritation or redness develops, get medical attention.

Eye Contact: Flush eyes with large amounts of water for 15 minutes. If irritation or other symptoms persist, get medical attention.



Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Danbury, CT 06810
Suite 300
Tel. 1-203-205-2900

Ingestion: Aspiration hazard. DO NOT induce vomiting. If the victim is fully conscious, have them rinse their mouth with water. Get immediate medical assistance by calling a doctor or poison center. Never give anything by mouth to a person who is unconscious or drowsy.

5. Firefighting Measures

Extinguishing Media: Use carbon dioxide, foam, water spray, or dry chemical.

Special Fire Fighting Procedures: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

Unusual Fire Hazards: Extremely flammable aerosol and liquid. Vapors are heavier than air and will travel along surfaces to remote ignition sources and flash back. Vapors may be explosive in confined areas. Vapor will collect in low lying areas. Contents under pressure. Closed containers may rupture if exposed to extreme heat.

Hazardous Combustion Products: Thermal decomposition will generate oxides of carbon.

6: Accidental Release Measures

Personal Precautions: Eliminate all sources of ignition. Ventilate area with explosion proof equipment. Wear appropriate protective clothing and equipment as described in section 8.

Environmental Precautions: Prevent entry in storm sewers and waterways. Report spill as required by local and national regulations.

Methods for Containment and Clean-Up: Place leaking can in a pail in a well ventilated area away from ignition sources until pressure has dissipated. Collect liquid using non-combustible absorbents and place into a suitable container for disposal. Use non-sparking tools and equipment.

7. Handling and Storage

Avoid contact with eyes. Avoid prolonged contact with skin, and clothing. Avoid breathing vapors or aerosols. Use with adequate ventilation. Keep away from heat, sparks, hot surfaces and open flames. Do not smoke while using. Do not spray on hot surfaces or electrical equipment. Wash thoroughly with soap and water after handling. Keep out of the reach of children. Do not puncture or incinerate containers.

Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol.

8. Exposure Controls / Personal Protection

CHEMICAL	EXPOSURE LIMIT
Propane	1000 ppm TWA OSHA PEL 1000 ppm TWA ACGIH TLV (aliphatic hydrocarbon gas)
VM&P Naphtha	None Established
Heptane (As Heptane isomer)	500 ppm TWA OSHA PEL 400 ppm TWA ACGIH TLV, 500 ppm STEL
N-Butane	1000 ppm TWA ACGIH TLV (aliphatic hydrocarbon gas)
Xylene	100 ppm TWA OSHA PEL 100 ppm TWA ACGIH TLV, 150 ppm STEL



Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Danbury, CT 06810
Suite 300
Tel. 1-203-205-2900

Methyl Ethyl Ketone	200 ppm TWA OSHA PEL 200 ppm TWA ACGIH TLV, 300 ppm STEL
Methyl n-Amyl Ketone	100 ppm TWA OSHA PEL 50 ppm TWA ACGIH TLV
Ethyl benzene	100 ppm TWA OSHA PEL 20 ppm TWA, 125 ppm STEL ACGIH TLV

Ventilation: Use only with ventilation equivalent to outdoors. For operations where the TLV may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits. Use explosion proof equipment where required.

Respiratory Protection: For operations where the TLV may be exceeded, a NIOSH approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

Gloves: Impervious gloves are recommended if needed to avoid contact.

Eye Protection: Avoid eye contact. Safety glasses or goggles are recommended if eye contact is possible.

Other Protective Equipment/Clothing: Use protective equipment if needed to avoid skin contact and contamination of personal clothing.

9. Physical and Chemical Properties

Appearance And Odor: Syrupy white liquid with a solvent odor in an aerosol can.

pH: Not determined	Specific Gravity: 0.675
Boiling Point: <1 -285°F (<-17.2 -- 140.5°C)	Vapor Pressure: 750 mm Hg @ 20°C
Freezing Point: Not determined	Vapor Density: (Air = 1) >1
Solubility In Water: Insoluble	Percent Volatile: 87.2957%
Viscosity: Not determined	Evaporation Rate: (Butyl Acetate = 1) >4.6
Coefficient Of Water/Oil Distribution: Not determined	Autoignition Temp: Not determined
Flash Point: < -25°F (<31.6°C) (Propellant)	Propellant is a flammable gas.
Flammability Limits: LEL: 0.9%	UEL: 11.5%

10. Stability and Reactivity

Stability: Stable

Conditions To Avoid: Avoid heat, sparks, open flames, and direct sunlight. Do not puncture container.

Incompatibility: Strong oxidizing agents, reducing agents and acids.

Hazardous Decomposition Products: Thermal decomposition will generate oxides of carbon.

11. Toxicological Information

Acute Hazards:

Inhalation: Inhalation of vapors may cause upper respiratory tract irritation with coughing and sneezing. High vapor concentrations may cause headache, dizziness, weakness, nausea and vomiting.



Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Danbury, CT 06810
Suite 300
Tel. 1-203-205-2900

Skin Contact: May cause irritation. Prolonged skin contact may defat the skin and produce dermatitis.

Eye Contact: Direct contact may cause eye irritation with redness and tearing.

Ingestion: Aspiration hazard. Aspiration into the lungs during swallowing or vomiting may result in severe lung damage which may be fatal. Swallowing may cause gastrointestinal effects such as nausea, vomiting and diarrhea and central nervous system effects.

Chronic Hazards: Prolonged or repeated overexposure may cause adverse effects on the nervous system, blood, kidneys, and liver.

Medical Conditions Aggravated By Exposure: Existing skin, liver, kidney, nervous system, and blood disorders.

Carcinogen: Ethyl benzene is classified by IARC as a possible human carcinogens (group 2B). None of the other components are listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

Propane: LC50 Rat inhalation >800,000 ppm

N-Butane: LC50 Rat inhalation 658 mg/m³/4 hr

Xylene: LD50 Rat oral 4,300 mg/kg; LD50 Rabbit skin > 1,700 mg/kg; LC50 Rat inhalation >5,000 ppm/4 hr

Methyl Ethyl Ketone: LD50 Rat oral 3,400 mg/kg; LD50 Rabbit skin > 8,000 mg/kg;

LC50 Rat inhalation >5,000 ppm/6 hr

Methyl n-Amyl Ketone: LD50 Rat oral 1,670 mg/kg; LD50 Rabbit skin 12,600 mg/kg

Ethyl benzene: LD50 Oral Rat: 3500 mg/kg; LD50 Skin Rabbit >17,800 mg/kg

12. Ecological Information

No ecotoxicity data is currently available for product.

Xylene: 24 hr LC50 daphnia magna 150 mg/L; 96 hr EC50 Lepomis macrochirus (bluegill) 12.0 mg/L;

96 hr LC50 Fathead minnow 26.7 mg/mL

Methyl Ethyl Ketone: 48 hr EC50 daphnia magna 1382 mg/L; 96 hr EC50 Lepomis macrochirus (bluegill) 1690 mg/L

Methyl n-Amyl Ketone: 96 hr LC50 Fathead minnow 131 mg/mL

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

Do not incinerate or place container into trash compactor.

14. Transport Information

DOT Hazardous Materials Description:

Until December 31, 2013: Consumer Commodity ORMD

After January 1, 2014: UN1950, Aerosols, 2.1 Limited Quantities

Canadian TDG Hazardous Materials Description: Consumer Commodity. Limited Quantity.

IMDG Dangerous Goods Description: UN1950, Aerosols, 2.1



Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Danbury, CT 06810
Suite 300
Tel. 1-203-205-2900

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has an RQ of 1,428 lbs based on the RQ for xylene of 100 lbs present at 7% maximum. Oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Sudden Release of Pressure, Acute Health, Chronic Health, Fire Hazard

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Xylene	7%	(CAS# 1330-20-7)
Ethylbenzene	2%	(CAS# 100-41-4)

Canada:

Canadian WHMIS Classification: Class B-5 (Flammable Aerosol), Class D - Division 2 - Subdivision A - (Very toxic material causing other toxic effects)

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian DSL.

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Rating (NFPA 704):	Health: 2	Fire: 4	Instability: 0
HMIS Rating:	Health: 2*	Fire: 4	Physical Hazard: 0

REVISION SUMMARY: 01/31/2013: Change to section 1.

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH