



Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

1. Product And Company Identification

Product Name: STP® High Mileage Oil Treatment

Responsible Party: The Armor All/STP Products Company
44 Old Ridgebury Road
Suite 300
Danbury, CT 06810

Information Phone Number: +1 203-205-2900

Emergency Phone Number:

For Medical Emergencies, call 1-866-949-6465 / +1 303-389-1332 (Outside US and Canada)
For Transportation Emergencies, call 1-800-424-9300 (Chemtrec) +1-703-527-3887 for
Outside US and Canada (call collect)

MSDS Date Of Preparation: 09/10/14

Product Use: Automotive maintenance product – For consumer and professional use

2. Hazards Identification

EMERGENCY OVERVIEW

CAUTION: Eye irritant. Inhalation of mists or vapors generated at elevated temperatures may cause respiratory irritation. Prolonged skin contact may cause dryness and defatting.

3. Composition/Information On Ingredients

Component	CAS No.	Amount
Mineral Oil	Mixture	60-100%
Zinc alkyl dithiophosphate	68649-42-3	1- <5%
Branched alkylphenol	Proprietary	0.1- <1%

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. If breathing has stopped, administer artificial respiration. Get medical attention if symptoms appear and persist.

Skin Contact: Remove contaminated clothing and launder before reuse. Wash exposed skin with soap and water. If skin irritation or redness develops, get medical attention.

Eye Contact: Flush eyes with large amounts of water for 15 minutes. If irritation or other symptoms persist, get medical attention.

Ingestion: DO NOT induce vomiting. If the victim is fully conscious, have them rinse their mouth with water. Get medical assistance by calling a doctor or poison center. Never give anything by mouth to a person who is unconscious or drowsy.

5. Firefighting Measures

Extinguishing Media: Use water fog, foam, carbon dioxide or dry chemical. Cool fire exposed containers with water.

Special Fire Fighting Procedures: Firefighters should wear positive pressure self-contained breathing apparatus
STP® High Mileage Oil Treatment



Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

and full protective clothing for fires in areas where chemicals are used or stored.

Unusual Fire Hazards: Closed containers may rupture if exposed to extreme heat.

Hazardous Combustion Products: Burning may produce carbon monoxide and carbon dioxide, zinc oxide and hydrogen sulfide.

6: Accidental Release Measures

Personal Precautions: Caution – slip hazard. Eliminate all ignition sources and ventilate the area. Wear appropriate protective equipment.

Environmental Precautions: Prevent entry in storm sewers and waterways. Report spill as required by local and national regulations. Notify the National Response Center if a spill of any amount enters navigable waters, the contiguous zone, or adjoining shorelines.

Methods for Containment and Clean-Up: Stop spill at the source if it is safe to do so. Absorb with an inert material. Collect into a suitable container for disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard.

7. Handling and Storage

Avoid contact with eyes. Avoid prolonged contact with skin and clothing. Avoid breathing vapors and mists. Wash exposed skin thoroughly with soap and water after use. Keep containers closed when not in use. Do not permit smoking in use or storage areas. Keep out of the reach of children.

Store in a cool, dry, well ventilated area. Store away from oxidizing agents and other incompatible materials.

Empty containers retain product residue and may be hazardous. Do not reuse empty containers.

8. Exposure Controls / Personal Protection

CHEMICAL	EXPOSURE LIMIT
Mineral Oil	5 mg/m ³ inhalable TWA ACGIH TLV 5 mg/m ³ TWA OSHA PEL
Zinc alkyl dithiophosphate	None Established
Branched alkylphenol	None Established

Ventilation: General ventilation should be adequate for all normal use. For operations where the TLV may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.

Respiratory Protection: None under normal use conditions. For operations where the TLV is exceeded, a NIOSH approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

Gloves: Impervious gloves such as neoprene or nitrile are recommended if needed to avoid prolonged or repeated skin contact.

Eye Protection: Safety glasses or goggles are recommended if eye contact is possible.

Other Protective Equipment/Clothing: Appropriate protective clothing as needed to prevent prolonged/ repeated skin contact.



Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

9. Physical and Chemical Properties

Appearance And Odor: Light brown liquid with a petroleum-like odor.

pH: Not applicable	Specific Gravity: 0.8744
Boiling Point: Not determined	Vapor Pressure: Not determined
Freezing Point: Not determined	Vapor Density: Not determined
Solubility In Water: Insoluble	Percent Volatile: >95%
Viscosity: 3150 cSt @ 40°C	Evaporation Rate: Not determined
Coefficient Of Water/Oil Distribution: Not determined	Autoignition Temp: Not Determined
Flash Point: 275°F (135°C) PMCC	
Flammability Limits: LEL: Not determined	UEL: Not determined

10. Stability and Reactivity

Stability: Stable

Conditions To Avoid: Keep away from excessive heat and open flames.

Incompatibility: Strong oxidizing agents and reducing agents.

Hazardous Decomposition Products: Burning may produce carbon monoxide, carbon dioxide, zinc oxide and hydrogen sulfide.

11. Toxicological Information

Acute Hazards:

Inhalation: Inhalation of mists or vapors generated at elevated temperatures may cause upper respiratory tract irritation.

Skin Contact: Not a skin irritant. Prolonged or repeated contact may cause defatting and drying of the skin and dermatitis.

Eye Contact: Direct contact may cause eye irritation with redness, tearing and pain.

Ingestion: Swallowing may cause gastrointestinal irritation with nausea, vomiting and diarrhea.

Chronic Hazards: In oral studies with laboratory animals, an ingredient caused effects on the liver and thyroid.

Medical Conditions Aggravated By Exposure: Because of its defatting properties, this product may aggravate an existing dermatitis.

Carcinogen: None of the components is listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

Mineral Oil: LD50 Oral Rat: >5,000 mg/kg; LD50 Skin Rabbit: >5000 mg/kg

Zinc alkyl dithiophosphate: LD50 Oral Rat: 2230-3100 mg/kg; LD50 Skin Rat >2000 mg/kg

12. Ecological Information



Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

No ecotoxicity data is currently available. This product is harmful to aquatic life with long-lasting effects. This product contains components which may be persistent in the environment.

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations.

14. Transport Information

DOT Hazardous Materials Description: Not Regulated

Canadian TDG Hazardous Materials Description: Not Regulated

IMDG Dangerous Goods Description: Not Regulated

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has no RQ, however, oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): Zinc compounds 1 - <5%

Canada:

Canadian WHMIS Classification: Class D - Division 2 - Subdivision B - (Toxic material causing other toxic effects)

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian Domestic Substances List.

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

Other International:

China: All of the ingredients are listed on the Chinese chemical inventory.

European Union: All of the components of this product are listed on the European Inventory of New and Existing Chemical Substances (EINECS) inventory.

Australia: All of the ingredients of this product are listed on the Australian Inventory of Chemical Substances (AICS).

Japan: All of the components are listed on Japanese MITI inventory.

Korea: All of the components of this product are listed on the Korean Existing Chemical List (KECL).



® Material Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

Philippines: All of the components of this product are listed on the Philippine Inventory of Chemicals and Chemical Substances (PICCS).

16. Other Information

NFPA Rating (NFPA 704):	Health: 1	Fire: 1	Instability: 0
HMIS Rating:	Health: 1	Fire: 1	Reactivity: 0

REVISION SUMMARY: Revision update.

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH